

Ocean Inflatable Boats

6 great reasons to buy OceanNZ...

1. Great Handling
2. Rugged Design
3. Excellent Safety Features
4. Convenient & Easy to Transport
5. Affordable Price
6. Built With Robust Materials



Attention all outdoor loving Kiwis...

Finally a robust inflatable boat, designed in Italy for NZ's rugged conditions

Free Shipping! Within NZ

Key Points & Specs

Front Handle	Marine Plywood Transom
Towing Rings	Reinforced Cone End
Over pressure Relief Valve	V Hull with Double PVC Layer
Life Line	Keel Rubbing Stake
Oar lock & Aluminum Oars	Side Tube Rubbing Stake
Carrying Handle	Seam Double Layer Protect
Boat Handling Rings	Drain Valve, Spare Valve
Plywood Seat	Pump & Repair Kit



“...just thought i'd email you regard the an Ocean 360 we brought...We have used it for fishing, kneeboarding, biscuiting and just general exploring both in lakes and at sea. It's extremely stable even with 3 of us fishing from it...Regards, Craig

”

Contact Details

Phone: +64 (0)3 471 9931

Email: inflatableboatsnz@gmail.com

Web : www.oceaninflatables.co.nz

Ocean Series Specifications

		OCEAN 270	OCEAN 290	OCEAN 320	OCEAN 360	OCEAN 380	OCEAN 420	Features
Boat Size	Overall Length	8.10 feet / 2.7metres	9.5 feet / 2.9metres	10.5 feet / 3.2 metres	11.9 feet / 3.6metres	12.5 feet / 3.8metres	13.9 feet / 4.2metres	0.9 - 1.2mm PVC coated fabric
	Beam width	5 feet / 1.51 metres	5 feet / 1.51 metres	5 feet / 1.51 metres	5.5 feet / 1.68 metres	5.5 feet / 1.68 metres	6.3 feet / 1.9 metres	Keel chamber for V-hull
	Mid transom height	15inch	15inch	15 inch	15 inch	15 inch	15 inch	Two rear spray guard
	Transom made	1" (24mm) plywood	1" (24mm) plywood	1" (24mm) plywood	1" (24mm) plywood	1" (24mm) plywood	1" (24mm) plywood	Side spray guard
	Transom max width	1 - 3/4" w motor pads	1 - 3/4" w motor pads	1 - 3/4" w motor pads	2 - 1/4 / w motor pads	2 - 1/4 / w motor pads	2 - 1/4 / w motor pads	2 floorboard side joiners
	Inner length	72 inch / 181 cm	72 inch / 181 cm	82 inch / 208 cm	101 inch / 255 cm	101 inch / 255 cm	122 inch / 310cm	2 oar lock and oar holder
	Inner width	26.5 inch/ 67 cm	26.5 inch/ 67 cm	26.5 inch/ 67 cm	32 inch/80cm	32 inch/80cm	40 inch/102 cm	Two side motor pads
	Tube diameter	16.3 inch / 41.5cm	16.3 inch / 41.5cm	16.3 inch / 41.5cm	17.3 inch / 44 cm	17.3 inch / 44 cm	17.3 inch / 44 cm	One (1) ID plates
Flooring	Floor boards	4 pieces per set	4 pieces per set	4 pieces per set	5 pieces per set	5 pieces per set	5 pieces per set	
	Side joiners	2 pieces	2 pieces	2 pieces	4 pieces	4 pieces	4 pieces	Safety
Capacity	Passengers	3 adult & 1 child	3 adult & 1 child	4 adult & 1 child	5 adult & 1 Child	6 adults	7 adults	Multi-layer man-made seam
	Max loading	1067lbs / 474 kg	1122lbs / 510 kg	1248 lbs / 566 kg	1600lbs / 727 kg	1600lbs / 727 kg	2396lbs / 1087kgs	Individual air chambers
	Suggested motor type	15"short shaft	15"short shaft	15"short shaft	15"short shaft	15"short shaft	15"short shaft	Keel bottom double layer
	Max motor support	10HP / 7.5kw	10HP / 7.5kw	15 HP / 11.25kw	25 hp / 18.75 kw	25 hp / 18.75 kw	30hp / 22.00 kw	Bow & 2 side lifelines
	Max motor weight	110lbs / 50kg	110lbs / 50kg	132 lbs / 60kg	154lbs / 70kg	154lbs / 70kg	161lbs / 73kg	3" width side rub strake
Chambers	Chambers number	3 tube & 1 keel	3 tube & 1 keel	3 tube & 1 keel	3 tube & 1 keel	3 tube & 1 keel	3 tube & 1 keel	6" keel bottom rub strake
	Tube max pressure	3.6 PSI / 25kpa	3.6 PSI / 25kpa	3.6 PSI / 25kpa	3.6 PSI / 25kpa	3.6 PSI / 25kpa	3.6 PSI / 25kpa	3" transom bottom strake
	Keel max pressure	5 psi / 35kpa	5 psi / 35kpa	5 psi / 35kpa	5 psi / 35kpa	5 psi / 35kpa	5 psi / 35kpa	Enhanced transom joiner
	Over pressure valve	1 piece @ 4 PSI	1 piece @ 4 PSI	1 piece @ 4 PSI	1 piece @ 4 PSI	1 piece @ 4 PSI	1 piece @ 4 PSI	Anti-skid floor & seat
Handles	Front towing rings	2 side & 1 front	2 side & 1 front	2 side & 1 front	2 side & 1 front	2 side & 1 front	2 side & 1 front	1.5" diameter drain & valve
	Outside hand handle	1 pair (rear)	1 pair (rear)	1 pair (rear)	1 pair (rear)	1 pair (rear)	1 pair (rear)	fuel tank pad & string
	Inside d rings	2 pair (front & rear)	2 pair (front & rear)	2 pair (front & rear)	2 pair (front & rear)	2 pair (front & rear)	2 pair (front & rear)	
	Bow bag handles	four (4) d rings	four (4) d rings	four (4) d rings	four (4) d rings	four (4) d rings	four (4) d rings	Accessories
Oar & Seat	Bench seat	1 seat 34"x8"	1 seat 34"x8"	1 seat 34"x8"	2 seat 34"x8"	2 seat 34"x8"	2 seat 34"x8"	1x bow storage bag
	Seat patches	1 set / Front position	1 set / Front position	1 set / Front position	2 sets / dual position	2 sets / dual position	2 sets / dual position	1x seat bag & cushion (optional)
	Aluminum oar	2 pieces 5 ft long	2 pieces 5 ft long	2 pieces 5.3 ft long	2 pieces 5.3 ft long	2 pieces 5.3 ft long	2 pieces 5.3 ft long	1x boat carrying bag
Style	Bow design	Sharp nose	Sharp nose	Sharp nose	Sharp nose	Sharp nose	Sharp nose	1x foot pump
	Color combination	Blue, Red, Black, light, Grey	Blue, Red, Black, light, Grey	Blue, Red, Black, light, Grey	Blue, Red, Black, light, Grey	Blue, Red, Black, light, Grey	Blue, Red, Black, light, Grey	1x Repair kit & air valve
	N American standard	max 3 feet wave	max 3 feet wave	max 4 feet wave	max 6 feet wave	max 6 feet wave	max 6 feet wave	1 x towing string
Packing	Boat net weight	105lbs / 48kg	105lbs / 48kg	115lbs / 53kg	160lbs / 73 kgs	160lbs / 73 kgs	180lbs / 82kgs	1x air valve connector
	Shipping weight	115lbs / 53kg	115lbs / 53kg	125lbs / 57 kgs	180lbs / 82 kg	180lbs / 82 kg	200lbs / 90kgs	User manual
	Package size	1 package	1 package	1 package	1 package	1 package	1 package	certificate of origin
	Total cubage	0.26CBM	0.26CBM	0.26 cbm	0.38 cbm	0.38 cbm	0.45cbm	